

DECLARATION OF PERFORMANCE NO C/027/4




1. The unique identification code of the product type: **WPP/WIZ C/027/4 COROTOP METAL 440**
2. Intended use: **Flexible sheets for underlays which are to be used under roof covering of discontinuous roofs and for walls which are to be used in walls behind outside wall coverings in order to avoid penetration of wind and water from outside**
3. Manufacturer: **CB S.A., ul. Ozimska 2a, PL 46-053 Chrzastowice**
4. The system of assessment and verification of constancy of performance: **System 3**
5. The harmonized standard: **EN 13859-1:2010, EN 13859-2:2010**
The notified body **No 1434, Polskie Centrum Badań i Certyfikacji S.A. (PCBIC)**
6. Declared properties:

Characteristics	Unit	Performance	Tolerance	Harmonized technical specification
Reaction on fire	Class	E	-	4.3.1 EN 13859-1:2010 4.3.1 EN 13859-2:2010
Resistance to water penetration	Class	W1	-	4.3.2 EN 13859-1:2010 4.3.2 EN 13859-2:2010
Mechanical properties after stretching				
Tensile strenght along MD	[N/50mm]	320	±30%	4.3.4 EN 13859-1:2010 4.3.5 EN 13859-2:2010
Tensile strenght across CD	[N/50mm]	200	±30%	4.3.4 EN 13859-1:2010 4.3.5 EN 13859-2:2010
Elongation along MD	[%]	75	±30%	4.3.4 EN 13859-1:2010 4.3.5 EN 13859-2:2010
Elongation across CD	[%]	100	±30%	4.3.4 EN 13859-1:2010 4.3.5 EN 13859-2:2010
Tear property				
Tear resistance along MD	[N]	210	±20%	4.3.5 EN 13859-1:2010 4.3.6 EN 13859-2:2010
Tear resistance across CD	[N]	270	±20%	4.3.5 EN 13859-1:2010 4.3.6 EN 13859-2:2010
Flexibility at low temperature	[°C]	≥-40	-	4.3.7 EN 13859-1:2010 4.3.8 EN 13859-2:2010
Resistance to artificial aging associated with mechanical properties				
Tensile strenght along MD	[N/50mm]	NPD	-	4.3.8 EN 13859-1:2010 4.3.9 EN 13859-2:2010
Tensile strenght across CD	[N/50mm]	NPD	-	4.3.8 EN 13859-1:2010 4.3.9 EN 13859-2:2010
Elongation along MD	[%]	NPD	-	4.3.8 EN 13859-1:2010 4.3.9 EN 13859-2:2010
Elongation across CD	[%]	NPD	-	4.3.8 EN 13859-1:2010 4.3.9 EN 13859-2:2010
Resistance to artificial aging associated with resistance to water penetration	Class	NPD	-	4.3.8 EN 13859-1:2010 4.3.9 EN 13859-2:2010
Water vapor resistance	[m]	0,02	[-0,01/ +0,03]	4.3.3 EN 13859-2:2010

The performance characteristics of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 the sole responsibility of the manufacturer's specified above.

On behalf of the manufacturer signed: **Piotr Górski – Member of the Board CB S.A.**

Chrzastowice, dn. 18.04.2018


(signature)

CB Spółka Akcyjna
ul. Ozimska 2A
46-053 Chrzastowice
www.cb.com.pl
e-mail: sekretariat@cb.com.pl

Zarząd:
Prezes Zarządu: Jerzy Górski
Członek Zarządu: Piotr Górski
Wartość kapitału akcyjnego
1 175 550,00 zł

KRS 0000320862
NIP 754-10-13-532
Regon 530993551
Raiffeisen Bank Polska S.A.
07 1750 1194 0000 0000 1205 0917

Chrzastowice
tel.: +48 77 400 50 62; +48 77 400 50 70-71
fax: +48 77 400 50 72; +48 77 400 50 78

...być profesjonalistą i nieść sukces