

DataSheet DELTA®-TAPE FAS

Product name	DELTA®-TAPE FAS 60 DELTA®-TAPE FAS 100
Dimensions	60 mm / 100 mm / 230 mm width by 20 m length
Delivery form	DELTA®-TAPE FAS 60 - 10 rolls / box; 85 boxes / palett DELTA®-TAPE FAS 100 - 6 rolls / box; 85 boxes / palett
Material	Solvent-free pure acrylic adhesive. Highly UV-resistant backing.
Properties	Single side bonding adhesive tape with high ageing resistance and extreme adhesive strength.
Field of application	Especially designed for use with DELTA-FASSADENBAHNEN. For sealing overlaps, penetrations, and difficult details.
Consumption	Approx. 1 m / metre overlap
Storage	At least 2 years in original box, light protected, cool and dry at temperatures between + 5°C and + 30°C
Application climate	From + 5°C (with tape being stored at recommended conditions)
Setting time	none
Functional temperature range	-40 bis +80°C
General advices	Surfaces have to be clean, dry, free of dust, grease and frost as well as sufficiently load-bearing.
Special advices	The final performance and bonding establishes over time, depending on storage, underground and surrounding climate.
Date	03/2015
Originator	U.Goerke

The contents of this data sheet describes the current state of knowledge at the time of publication and does not purport to be complete. The information listed does not release from own responsibility.

With publication of this sheet all previous ones are no longer valid.. Errors and typing errors reserved.