

Description

Single sided LDPE tape.

Product data

Backing	100 µ LDPE film, white
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	µ	100	PSTC 133
Adhesion to steel	N/25mm	3.5	PSTC 101
Tensile strength MD	N/25mm	60	PSTC 131
Elongation at break	%	400	PSTC 131
Temp. Resistance	°C	60°C	=

Application

Multipurpose LDPE tape used in packaging related applications such as PE bag closure.

Features	Benefits	
Natural rubber and resins solvent based adhesive	✓ Good adhesion in most applications	✓ Moderately ageing resistant
White LDPE backing	✓ Good moisture and vapour barrier ✓ Hand tearable	✓ Very high elongation ✓ Adaptable to different surfaces

All technical data contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, nor can the information in itself be interpreted as a guarantee. Given the wide variety of applications of our products, the purchaser must question the suitability of the product(s) for each application and examine whether the intended products meet or can meet the set requirements. Before extensive use, the purchaser shall test the products. The purchaser shall bear exclusively all risks associated with the use of the products. Under no circumstances will Tape Service Coenraets be liable for any damage or costs incurred, nor for any indirect or accidental damage or costs incurred as a result of the use of the products.