

Data sheet DELTA® -DUO TAPE 38

Product name	DELTA® -DUO TAPE 38
Dimensions	Width 38 mm
Delivery form	Roll 38 mm x 50 m; 16 Rolls / Box ; 48 Boxes / Pallet
Material	Solvent-free pure acrylic adhesive, mesh-reinforced, with white/blue paper release
Properties	Double side bonding reinforced adhesive tape, extreme adhesive strength, easy tear off.
Field of application	For sealing and repairing sheets inside overlappings, especially all DELTA-sheets (always on the printed upper side) and for joints to similar surfaces and to other plastics (hard), metal and smooth wooden parts.
Restrictions	Bonding on rough wood and mineral surfaces and suchlike is not or only to a limited extent recommended. Do not use on low quality regenerated PE sheets and sheets including chlorinated paraffine, do not use in saunas.
Consumption	Approx. 1 m / metre overlap
Storage	At least 2 years in original box, light protected, cool and dry.
Storage climate	+ 5°C bis + 30°C
Application climate	From + 5°C (with tape being stored at recommended conditions)
Setting time	None
Functional temperature range	-40 bis +80°C
Processing instructions	Consider general application instructions DELTA®-KLEBEPROGRAMM, especially guideline DELTA®-MULTI BAND.
General advices	Surfaces have to be clean, dry, free of dust, grease and frost as well as sufficiently load-bearing. Non- sufficiently load-bearing, e.g. sandy undergrounds have to be primed with DELTA-AGF ALLGRUNDFIX. A surface tension of >38 mN/m should be present.
Special advices	The final performance and bonding establishes over time, depending on storage, underground and surrounding climate.
Date	03/2018
	NKL

Der Inhalt dieses Datenblattes gibt den aktuellen Kenntnisstand zum Zeitpunkt der Erstellung wider und erhebt keinen Anspruch auf Vollständigkeit. Die aufgeführten Angaben entbinden nicht von eigenverantwortlichem Handeln.

Mit Erscheinen dieses Blattes verlieren alle vorhergehenden ihre Gültigkeit. Irrtümer und Schreibfehler vorbehalten.