



Technical Adhesive Tapes



REFERENCE SELF C1425 SYSTEMIT

| | | |
|--------------------|----------------------------|-------------------|
| DESCRIPTION | Single-sided adhesive tape | |
| ADHESIVE | Type | Modified acrylic |
| LINER | Type | Siliconised paper |
| | Weight | 120 grs/sqm |
| | Colour | Brown |
| CARRIER | Type | Polyethylene film |
| | Colour | Printed SYSTEMIT |

PHYSICAL PROPERTIES

| | | |
|--|-----------------|--------------|
| ADHESIVE STRENGTH AFERA 5001 (N/25 mm): | Min.35N | |
| TACK FINAT-9 (N/6,25mm2) | Min.32N | |
| THICKNESS (mm without liner): | 0,29mm | + -7% |
| TEMPERATURE RESISTANCE (°C): | -30/ +80 | |

APPLICATIONS

Polyethylene adhesive tape coated with UV-resistant acrylic adhesive for external use. Specially designed for joining breathable membranes on overlap lines or side surfaces of windows for roofs, fireplaces, vents, etc., with the purpose of waterproofing, wind and steam in roof and wall systems

Shelf life and storage instructions

12 months from SELF, S.L. delivery time when stored in original boxes at temperature of 21°C and a relative humidity of 50%. The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

General points

SELF, S.L. recommends paying special attention to contact surfaces, checking that they are totally clear of grease, oil, dust or any other non-stick substance.

The technical data shown in this document are for the final user's guidance and therefore they do not constitute a legal warranty in relation to certain properties caused by numerous influences that may act during handling and use of our products.

Prior to use, purchasers should determine the suitability of this product for the specific purposes and assume all risk and liability in connection with them

P.I. Can Casablanacas, C/Berguedà, Esq.Priorat, nave 3, 08192,Sant Quirze del Vallès, Barcelona, Spain

Telf: +34 93 721 52 53

self@selfautoadhesivos.com

www.selfautoadhesivos.com

DOC.03010500