



REFERENCE SELF 1289

DESCRIPTION	Single-sided adhesive tape	
ADHESIVE	Туре	Modified acrylic
LINER	Туре	Siliconized paper
	Colour	Havana
	Weight	90grs/m2
CARRIER	Туре	Polypropylene non-woven + Pe film
	Colour	Black

PHYSICAL PROPERTIES

ADHESIVE STRENGTH AFERA 5001 (N/25 mm): 30 +-5 0,55 THICKNESS (mm without liner): +-12% -30/+80 TEMPERATURE RESISTANCE (°C): WATER VAPOUR TRANSMISSION (Sd) 17m UV RESISTANCE OUTDOOR EXPOSURE FOR UP 6 MONTHS

APPLICATIONS

Ínsulation in building construction. High adhesive coating weight. Excellent adhesion on irregular surfaces.

Shelf life and storage instructions
12 months from SELF, SL delivery time when stored in original boxes at temperature of 21°C and a relative humidity of 50%. The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

SELF,S.L. recommends paing special attention to contact surfaces, checking that they are totally clear of grease, oil, dust or any other non-stick substance.

The technnical data shown in this document are for the final user's guidance and therefore they do not constitute a legal warranty in relation to certain properties caused by numerous influences that may act during handling and use of our

Prior to use, purcharsers should determine the suitability of this product for the specific purposes and assume all risk and liability in connection with them

P.I. Can Casablancas, C/Berguedà, Esq. Priorat, nave 3, 08192, Sant Quirze del Vallés, Barcelona, Spain T/+34 93 721 52 53

E/ self@selfautoadhesivos.com

W/selfautoadhesivos.com